

FRONT TIRE



GREEN EX



BIAS TIRES FOR TRACTORS

- » Optimized rib design for easy driving both on and off roads
- » More rubber in raised center rib provides best direction stability
- » Strong sidewall ensures better stability in rough operation
- » Penetration resistant compound minimizes air leaking in tubeless tire

Tire Size	PR	TT/TL	Rim		Unloaded Inflated Dimension ± 2%				SLR		RC ± 2.5%		RCI	Tire Weight	Tire Weight	Tread Depth	Tread Depth
					S.W.		O.D.										
			Rec.	Alt.	mm	inch	mm	inch	mm	inch	mm	inch					
15"																	
5.00-15	4	TT	3.00D		130	5.1	664	26.1	307	12.1	1951	76.8	26	7.36	16.23	13	16
5.00-15	4	TL	3.00D		130	5.1	664	26.1	307	12.1	1951	76.8	26	7.99	17.61	13	16
5.00-15	6	TT	3.00D		130	5.1	664	26.1	307	12.1	1951	76.8	26	7.36	16.23	13	16
16"																	
5.50-16	6	TT	4.00E	3.5D,4.5E	157	6.2	719	28.3	330	13.0	2134	84.0	28	9.86	21.74	15	18
5.50-16	6	TL	4.00E	3.5D,4.5E	157	6.2	719	28.3	330	13.0	2134	84.0	28	10.53	23.21	15	18
6.00-16	6	TT	4.50E	4.00E,4.25KA	169	6.7	735	28.9	346	13.6	2190	97.8	28	10.55	23.26	19	24
6.00-16	6	TL	4.50E	4.00E,4.25KA	169	6.7	735	28.9	346	13.6	2190	97.8	28	10.53	23.21	15	18
6.00-16	8	TT	4.50E	4.00E,4.25KA	169	6.7	735	28.9	346	13.6	2190	97.8	28	11.01	24.27	19	24
6.00-16	10	TT	4.50E	4.00E,4.25KA	169	6.7	735	28.9	346	13.6	2190	97.8	28	12.28	27.07	19	24
6.50-16	6	TT	4.50E	4.00E,4.25KA	175	6.9	761	30.0	344	13.6	2295	90.4	29	12.30	27.12	19	24
7.50-16	8	TT	5.50F	6LB	203	8.0	808	31.8	366	14.4	2440	97.8	30	16.32	35.98	21	26
7.50-16	8	TL	5.50F	6LB	203	8.0	808	31.8	366	14.4	2440	97.8	32	17.23	37.99	21	26
10.00-16	8	TL	W8	W8L, 8LB	275	10.8	900	35.4	418	16.5	2682	105.6	34	29.23	64.44	29	36
11.00-16	8	TT	W 10 L	W 8, W 8 L	315	12.4	965	38.0	434	18.0	2893	114.0	34	33.15	73.08	30	38
11.00-16	10	TT	W 10 L	W 8, W 8 L	315	12.4	965	38.0	434	18.0	2893	114.0	34	36.26	79.94	30	38
18"																	
7.50-18	8	TT	5.50F	6LB	203	8.0	860	33.9	366	14.4	2440	97.8	30	18.57	40.94	21	26
19"																	
6.00-19	6	TT	4.50E	4.00E,4.25KA	169	6.7	814	32.0	382	15.0	2445	97.8	30	13.12	28.92	19	24
20"																	
7.50-20	8	TT	5.50F	5.00F	205.74	8.1	914	36.0	432	17.0	2718	107.0	32	19.35	42.66	21	26

30 kmph (20 mph)				40 kmph(25 mph)				Inflation Pressure		
Speed Symbol	Load Index	Max.Load		Speed Symbol	Load Index	Max.Load		psi	kpa	bar
		kgs	lbs			kgs	lbs			
A6	73	365	805	A8	70	335	740	44	280	2.8
A6	73	365	805	A8	70	335	740	44	280	2.8
A6	82	475	1045	A8	79	437	965	56	370	3.7
15"										
A6	86	530	1170	A8	78	425	940	56	370	3.8
A6	86	530	1170	A8	78	425	940	56	370	3.8
A6	88	560	1230	A8	85	515	1140	52	360	3.6
A6	88	560	1230	A8	85	515	1140	52	360	3.6
A6	94	670	1480	A8	91	615	1360	70	470	4.7
A6	98	750	1650	A8	95	690	1520	80	550	5.5
A6	91	615	1356	A8	88	560	1235	48	330	3.3
A6	103	875	1930	A8	99	775	1710	56	370	3.7
A6	103	875	1930	A8	99	775	1710	56	370	3.7
A6	118	1320	2910	A8	115	1215	2680	40	280	2.8
A6	121	1450	3195	A8	118	1320	2910	41	280	2.8
A6	125	1650	3640	A8	122	1500	3305	45	310	3.1
16"										
A6	106	950	2090	A8	102	850	1870	56	390	3.9
18"										
A6	93	650	1430	A8	89	580	1280	48	330	3.3
19"										
A6	109	1030	2270	A8	101	825	1820	56	340	3.4