

FLOTATION RADIAL



GREEN XLR

 **F77 (13)**

| Tire Size | LI/SS | Type | Rim | | Unloaded Inflated Dimension ± 2% | | | | SLR | | RC ± 2.5% | | RCI | SRI | Tire Weight | Tire Weight | Tread Depth | Tread Depth | | |
|-------------|-------------|------|----------|---------------------|----------------------------------|------|------|------|-----|------|-----------|-------|-----|-----|-------------|-------------|-------------|-------------|----|------|
| | | | Rec. | Alt. | S.W. | | O.D. | | mm | inch | mm | inch | | | | | | | mm | inch |
| | | | | | mm | inch | mm | inch | | | | | | | | | | | | |
| 22.5" | | | | | | | | | | | | | | | kgs | lbs | mm | 32nds | | |
| 560/60R22.5 | 161D/172 A8 | TL | AG 16.00 | 16.00, 17.00, AG 20 | 543 | 21.4 | 1244 | 49.0 | 549 | 21.6 | 3785 | 149.0 | 39 | 600 | 103 | 226 | 23 | 29 | | |
| 560/60R22.5 | 165D/176 A8 | TL | AG 16.00 | 16.00, 17.00, AG 20 | 543 | 21.4 | 1244 | 49.0 | 549 | 21.6 | 3785 | 149.0 | 39 | 600 | 103 | 227 | 23 | 29 | | |



FLOTATION RADIAL TIRES FOR HEAVY-DUTY TRAILERS

- » Offers high load carrying capacity at low inflation pressure
- » Lug contact at center line ensures smooth and comfortable run on the road
- » Strong nylon casing and special tread compound offers high wear resistance
- » Reinforced bead offers superior stability
- » Low rolling resistance leads to excellent fuel efficiency

| Maximum Load Capacity (lbs) | | | | | | | | | | Maximum Load Capacity (kgs) | | | | | | | |
|-----------------------------|------|-------|-------|-------|-------|-------|-------|-------|----------|-----------------------------|------|------|------|------|------|------|------|
| mph/psi | 17 | 23 | 29 | 35 | 40 | 46 | 52 | 58 | kmph/BAR | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
| 45 | 3900 | 4670 | 5490 | 6260 | 7020 | 7805 | 8545 | 9290 | 70 | 1770 | 2120 | 2490 | 2840 | 3185 | 3540 | 3875 | 4215 |
| 40 | 4280 | 5130 | 6025 | 6870 | 7710 | 8565 | 9380 | 10195 | 65 | 1945 | 2325 | 2735 | 3115 | 3495 | 3885 | 4255 | 4625 |
| 30 | 5180 | 6205 | 7290 | 8315 | 9325 | 10365 | 11350 | 12335 | 50 | 2350 | 2815 | 3305 | 3770 | 4230 | 4700 | 5150 | 5595 |
| 25 | 5835 | 6985 | 8210 | 9360 | 10500 | 11665 | 12780 | 13890 | 40 | 2645 | 3170 | 3725 | 4245 | 4765 | 5290 | 5795 | 6300 |
| 15 | 6765 | 8105 | 9520 | 10860 | 12180 | 13530 | 14820 | 16110 | 25 | 3070 | 3675 | 4320 | 4925 | 5525 | 6140 | 6725 | 7310 |
| 5 | 7710 | 9230 | 10845 | 12370 | 13875 | 15415 | 16885 | 18355 | 10 | 3495 | 4185 | 4920 | 5610 | 6295 | 6995 | 7650 | 8325 |
| mph/psi | 17 | 23 | 29 | 35 | 40 | 46 | 52 | 58 | kmph/BAR | 1 | 2 | 2 | 2 | 3 | 3 | 4 | 4 |
| 45 | 4240 | 5280 | 6010 | 6930 | 7860 | 8590 | 9410 | 10340 | 70 | 1925 | 2395 | 2725 | 3145 | 3565 | 3895 | 4270 | 4690 |
| 40 | 4660 | 5800 | 6590 | 7620 | 8630 | 9420 | 10340 | 11350 | 65 | 2115 | 2630 | 2990 | 3455 | 3915 | 4275 | 4690 | 5150 |
| 30 | 5640 | 7010 | 7980 | 9210 | 10450 | 11420 | 12510 | 13750 | 50 | 2560 | 3180 | 3620 | 4180 | 4740 | 5180 | 5675 | 6235 |
| 25 | 6340 | 7880 | 8960 | 10350 | 11740 | 12820 | 14050 | 15440 | 40 | 2875 | 3575 | 4065 | 4695 | 5325 | 5815 | 6375 | 7005 |
| 15 | 7360 | 9160 | 10420 | 12030 | 13650 | 14900 | 16340 | 17940 | 25 | 3340 | 4155 | 4725 | 5455 | 6190 | 6760 | 7410 | 8140 |
| 5 | 8390 | 10430 | 11860 | 13700 | 15540 | 16960 | 18610 | 20440 | 10 | 3805 | 4730 | 5380 | 6215 | 7050 | 7695 | 8440 | 9270 |