

LOADER



GRIP EX

 **LT100 (R4)**

Tire Size	PR	TT / TL	TRA	Rim		Unloaded Inflated Dimension ± 2 %				SLR		RC ± 2 %		RCI
				Rec. inch	Alt. inch	SW		OD		mm	inch	mm	inch	
						mm	inch	mm	inch					
18"														
12.5/80-18	12	TL	L2	W9	11	300	11.0	958	37.7	431	17.0	2813	111	33
12.5/80-18	14	TL	L2	W9	11	292	11.5	958	37.7	431	17.0	2813	111	33



GRIP EX

 **LT122 (L2)**

Tire Size	PR	TT / TL	TRA	Rim		Unloaded inflated Dimension ± 2%				SLR		RC ± 2 %		RCI
				Rec. inch	Alt. inch	SW		OD		mm	inch	mm	inch	
						mm	inch	mm	inch					
24"														
14.9-24	12	TL	R4	DW13	W12	378	14.9	1265	49.8	570	22.4	3800	149.6	39

BIAS TIRES BUILT FOR LOADERS

- » Suitable for backhoe loaders and compact loaders
- » Herringbone tread pattern offers high traction in toughest terrains
- » Center crown block provides better traction and accelerated movement for higher productivity

Tire Weight	Tire Weight	Tread Depth	Tread Depth	Maximum Load @40kmph (25 mph)				Inflation Pressure		
				Speed Symbol	Load Index	kgs	lbs	psi	kpa	bar
kgs	lbs	mm	32nds							
39.84	87.83	26	33	A6	129/142	2700	5950	54	370	3.7
40.66	89.64	26	33	A6	135/148	3150	6944	62	430	4.3

BIAS TIRES BUILT FOR BACKHOE AND COMPACT LOADERS

- » Suitable for backhoe loaders and compact loaders in all farming, digging and loading operations
- » Extra deep tread ensures increased puncture resistance and durability
- » Features excellent traction and stability as well as improved cut and chip resistance

Tire Weight	Tire Weight	Tread Depth	Tread Depth	Maximum Load @40kmph (25 mph)				Inflation Pressure		
				Speed Symbol	Load Index	kgs	lbs	psi	kpa	bar
kgs	lbs	mm	32nds							
68.13	150.20	33	41.6	A8	145	2900	5930.5	42	290	2.9